

SILVERWOOD SUBDIVISION

PART OF THE NORTHEAST 1/4, SECTION 9, T.12N. - R.4E.

SAGINAW TOWNSHIP, SAGINAW COUNTY, MICHIGAN

SPICER ENGINEERING COMPANY
SAGINAW, MICHIGAN
1972

CURVE DATA						
NO.	DELTA ANGLE	RADIUS	ARC	CHORD	CHORD BEARING	TANGENT
1	90°-34'-00"	30.00'	47.42'	42.64'	S.45°-12'-45" W.	30.30'
2	90°-34'-00"	63.00'	94.58'	89.54'	S.45°-12'-45" W.	63.63'
3	90°-34'-00"	96.00'	151.75'	136.43'	S.45°-12'-45" W.	96.95'
4	90°-34'-00"	30.00'	47.42'	42.64'	N.45°-12'-45" E.	30.30'
5	90°-34'-00"	63.00'	94.58'	89.54'	N.45°-12'-45" E.	63.63'
6	90°-34'-00"	96.00'	151.75'	136.43'	N.45°-12'-45" E.	96.95'

1. ALL DIMENSIONS ARE GIVEN IN FEET.
2. ALL CURVILINEAR MEASUREMENTS ARE ARC DISTANCES.
3. CONCRETE MONUMENTS HAVE BEEN PLACED AT ALL POINTS MARKED "O"
4. SET SOLID IRON BARS 1/2" IN DIA. BY 18" IN LENGTH AT ALL LOT CORNERS.
5. BEARINGS ARE TRUE AS DETERMINED FROM AN OBSERVATION OF POLARIS ON MARCH 12, 1970
6. (R) INDICATES A RADIAL LINE
7. (3) INDICATES CURVE NUMBER (SEE CURVE TABLE HEREON)
8. ALL RECORDED BEARINGS OF ADJOINING PLATS ARE SHOWN HEREON.

